



Arctic Fox LLC—570 South 7th Street—Delano, Minnesota 55328 USA  
 Phone: (800) 654-5382 or (763) 972-2758—Fax: (763) 972-2873—[www.arctic-fox.com](http://www.arctic-fox.com)

Arctic Fox Europe—Strijmaden 5—4703 Roosendaal—The Netherlands  
 Phone: 31 (0) 165 55 9245—Fax: 31 (0) 165 54 9640—[www.arctic-foxeurope.eu](http://www.arctic-foxeurope.eu)

## Electric Fluid Reservoir Heaters

### 12 / 24 Volts DC—120 / 220 Volts AC



- Easy Peel-And-Stick application with pressure sensitive adhesive.
- May be installed in sub-zero temperatures.
- Mounts to any smooth, metal surface.
- No need to cut hoses, remove plugs, or lose anti-freeze or oil.
- Aluminum backing provides even heat distribution.
- Reduces pump cavitation, blown seals and burst hydraulic components.
- Reduces engine wear by improving the flow of engine oil.
- Models available in 120 and 240 VAC as well as 12 & 24 VDC.

DESCRIPTION				APPLICATION RANGE				
PART NUMBER	WATTS VOLTS	AMP. DRAW	INCHES MM	ENGINE OIL	DIESEL FUEL	WATER	HYDRAULIC OIL	POWER PLUG
EH-2801	125 120 AC	1	2.25 X 4 57 X 102	1.5-4 qt. 1.3-3.8L	N/A	5-20 gal. 18.9-75.7 L	1-10 gal. 3.8-37.9 L	3-Prong NEMA 5-15P
EH-2802	250 120 AC	2.1	3.5 X 4.5 89 X 114	4.5-12 qt. 4.3-11.4 L	N/A	24-45 gal. 90.9-170.3 L	10-30 gal. 37.9-113.6 L	3-Prong NEMA 5-15P
EH-2805	500 120 AC	4.2	5 X 7 127 X 178	3-6 gal. 11.4-22.7 L	40-60 gal. 151.4-227.1 L	50-100 gal. 189.2-378.5 L	20-50 gal. 75.7-189.3 L	3-Prong NEMA 5-15P
EH-2810	1000 120 AC	8.3	6 X 10.75 152 X 273	6.5-12 gal. 24.6-45.4 L	50-100 gal. 189.3-378.5 L	100-200 gal. 378.5-757 L	50-100 gal. 189.3-378.5 L	3-Prong NEMA 5-15P
EH-3201	125 220 AC	0.1	2.25 X 4 57 X 102	1.5-4 qt. 1.3-3.8 L	N/A	5-20 gal. 18.9-75.7 L	1-10 gal. 3.8-37.9 L	NONE
EH-3202	250 220 AC	1.1	3.5 X 4.5 89 X 114	4.5-12 qt. 4.3-11.4 L	N/A	24-45 gal. 90.9-170.3 L	10-30 gal. 37.9-113.6 L	NONE
EH-3205	500 220 AC	2.3	5 X 7 127 X 178	3-6 gal. 11.4-22.7 L	40-60 gal. 151.4-227.1 L	50-100 gal. 189.2-378.5 L	20-50 gal. 75.7-189.3 L	NONE
EH-3210	1000 220 AC	4.5	6 X 10.75 152 X 273	6.5-12 gal. 24.6-45.4 L	50-100 gal. 189.3-378.5 L	100-200 gal. 378.5-757 L	50-100 gal. 189.3-378.5 L	NONE
EH-2874	80 12 DC	6.7	1.5 X 8 38 X 203	N/A	N/A	3-12 gal. 11.4-45.4 L	.5-6 qt. .5-5.7 L	NONE
EH-3659	250 12 DC	20.8	5 X 5 127 X 127	N/A	N/A	24-45 gal. 90.9-170.3 L	10-30 gal. 37.9-113.6 L	NONE
EH-3660	370 12 DC	30.8	7 X 5 178 X 127	N/A	N/A	35-65 gal. 132.5-246.1 L	15-45 gal. 56.8-170.3 L	NONE
EH-4111	80 24 DC	3.4	4 X 1.5 101 X 38	N/A	N/A	3-12 gal. 11.4-45.4 L	.5-6 qt. .5-5.7 L	NONE
EH-4608	80 12 DC	6.7	3.25 X 1.75 83 X 45	N/A	N/A	3-12 gal. 132.5-246.1 L	.5-6 qt. .5-5.7 L	NONE
EH-6282	7 12 DC	0.6	1 X 2 25 X 51	Typical Application: spot heating for small valves or fittings				NONE

**NOTE:**

- When properly installed, heaters may be operated continuously if necessary.
- Typical operation time is three to five hours.
- Heaters may be used with a timer of the proper capacity to control operation time.
- Actual temperature of the fluid being heated cannot be calculated, and will vary with the fluid type, fluid volume, tank material and size, protection from heat loss, as well as climate conditions.